

Room Alert® 3S

“Temperature & Environment Monitoring...
Made Easy!”

The screenshot displays the Room Alert Monitor web interface. The top navigation bar includes 'Status', 'Digital Sensors', 'Switch Sensors', 'Light Tower & Relay', 'Alerting Sensors', 'Settings', and 'Help'. The main content area shows a dashboard for device RA3S-7009DD, including account status, a 'Data Center Temperatures' line graph, and a list of alerts such as 'Data Center Hot Warning' and 'RA12 No Power'. A physical red Room Alert 3S monitor is shown in the foreground, featuring a 'Room Alert 3S Environment Monitor' label and a 'NEW' starburst graphic.

Order Now For...

\$275

Room Alert 3S RA3S-ES0-BAS



Advanced Security Features, Small Footprint & Low Price

- Secure data transfer options include HTTPS / SSL Web Interface, SSL / TLS Email Support, SNMP v1/v2c/v3, 2048-bit encryption and SSL Push to Room Alert Account.
- Easy Ethernet ‘Plug & Play’ setup for immediate IT & facilities environment monitoring.
- Includes a built-in sensor for digital temperature and “PUSH” technology.
- Includes Power over Ethernet (PoE) built-in and a 5V Power Adapter.
- Includes ports for 1 digital sensor or Light Tower & Relay Adapter and 1 switch sensor or dry contact.
- Offers advanced alerting by email, email-to-SMS, SNMP, webpage update and more.
- Use Room Alert 3S’s built-in web server, RoomAlert.com Account, local Room Alert Manager software, or SNMP to monitor across your network.
- The Room Alert 3S package allows real-time sensor status, data logging, graphing, advanced alerting, Fahrenheit/Celsius, high/low watermarks and much more.
- Install in minutes today, enjoy ‘Peace Of Mind’ tonight!

5 Steps To Prevent EM Disaster

- 1) Install Monitors for Immediate Detection
- 2) Auto Alerting to Responsible IT Staff
- 3) Auto Shutdown & Action Procedures
- 4) Fast & Appropriate Response by Staff
- 5) Review/Analyze/Plan Future Prevention

Manufacturer: AVTECH Software, Inc.

AVT-220101.04

INCLUDES: Room Alert 3S ID Box (0U, 3-5/8" L x 1-3/4" W x 1" H), built-in Digital Temperature Sensor, 1 external Digital Sensor Port (RJ-11), 1 Switch Sensor Channel, Factory Reset Button, Power over Ethernet (PoE), PUSH technology, Ethernet Connection (RJ-45), 10' (3.1m) Ethernet cable, 5V Power Adapter (110/240 V, RoHS), built-in web server, SNMP Trap & Query enabled, SNMP MIB, downloadable *Room Alert User's Guide & Reference Manual*, 1 Year of RoomAlert.com Personal account access with free 90 day Professional upgrade (with any Room Alert monitor purchase), Room Alert Manager software available on Professional tier or higher, lifetime support, lifetime firmware updates, 3 year limited warranty from date of purchase. Optional sensors, Light Tower & Relay Adapter, GSM modem & RoomAlert.com upgrade options available.